

Jacksons Fencing
NBS Specification

Standard Posts

Manufacturer: Jacksons Fencing.
Web: www.jacksons-fencing.co.uk.
Tel: +44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Standard Post.

•Type:

-Standard panel posts:

[Not required].

[640006]. - Post length 2700 mm.

[640100]. - Post length 1200 mm.

[640200]. - Post length 1500 mm.

[640300]. - Post length 1800 mm.

[640400]. - Post length 2100 mm.

[640500]. - Post length 2400 mm.

-Heavy duty posts:

[Not required].

[641100]. - Post length 1200 mm.

[641200]. - Post length 1500 mm.

[641300]. - Post length 1800 mm.

[641400]. - Post length 2100 mm.

[641500]. - Post length 2400 mm.

[641600]. - Post length 2700 mm.

•Accessories:

(AND)

[640660]. - Chamfered post cap for use with 125 x 125 mm posts.

[640900]. - Chamfered post cap for use with 75 x 75 mm posts.

[641000]. - Chamfered post cap for use with 100 x 100 mm posts.

[645400BM]. - 75 mm ball and collar for use with 75 x 75 mm posts.

[645600BM]. - Small acorn for use with 75 x 75 mm posts.

[645700BM]. - Large acorn for use with 100 x 100 mm posts.

[645880BM]. - Compact ball and collar for use with 100 x 100 mm posts.

[667700]. - 1875 x 120 x 25 mm capping.

[667770]. - 1925 x 120 x 25 mm capping.

[668000]. - Half round post cap for use with 100 x 100 mm posts.

Options

Type:

- Various heights are available: 1200–3600 mm.
- Standard posts: 75 x 75 mm.
- Heavy Duty posts: 100 x 100 mm.

Standard square section posts without the unique slot that Jakposts incorporate.
All timber used throughout is superior quality Jakcured softwood guaranteed for 25 years.

Jacksons Fencing
NBS Specification
Installation
In accordance to manufacturers instructions